



US007423644B2

(12) **United States Patent**
Goel et al.

(10) **Patent No.:** **US 7,423,644 B2**
(45) **Date of Patent:** **Sep. 9, 2008**

(54) **METHOD AND APPARATUS FOR DUAL PASS ADAPTIVE TESSELLATION**

(75) Inventors: **Vineet Goel**, Winter Park, FL (US);
Stephen L. Morein, Cambridge, MA (US); **Robert Scott Hartog**,
Windermere, FL (US)

(73) Assignee: **ATI Technologies Inc.**, Markham,
Ontario (CA)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **11/428,756**

(22) Filed: **Jul. 5, 2006**

(65) **Prior Publication Data**

US 2006/0238535 A1 Oct. 26, 2006

Related U.S. Application Data

(63) Continuation of application No. 10/790,952, filed on
Mar. 2, 2004, now Pat. No. 7,109,987.

(51) **Int. Cl.**
G06T 15/30 (2006.01)

(52) **U.S. Cl.** **345/423**; 345/419; 345/502;
345/505; 345/506; 345/519; 345/532; 345/536;
345/539

(58) **Field of Classification Search** 345/419,
345/423, 502, 505, 506, 519, 532, 536, 538
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,821,940 A 10/1998 Morgan et al.

FOREIGN PATENT DOCUMENTS

EP 0930582 A2 7/1999

* cited by examiner


Primary Examiner—Kimbinh T Nguyen

(74) *Attorney, Agent, or Firm*—Vedder Price P.C.

(57) **ABSTRACT**

A method and apparatus for dual pass adaptive tessellation includes a vertex grouper tessellator operably coupled to receive primitive information and an index list and a shader processing unit coupled to the vertex grouper tessellator. During a first pass, the shader processing unit receives primitive indices generated from the primitive information and an auto-index value for each of the plurality of primitive indices. The method and apparatus further includes a plurality of vertex shader input staging registers operably coupled to the shader sequence, wherein the plurality of vertex shader input staging registers are coupled to a plurality of vertex shaders such that in response to a shader sequence output, the vertex shaders generate tessellation factors. The tessellation factors are provided to the vertex grouper tessellator such that the vertex grouper tessellator generates a per-process vector output, a per primitive output and a per packet output during a second pass.

5 Claims, 4 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5

1

METHOD AND APPARATUS FOR DUAL PASS ADAPTIVE TESSELLATION

RELATED CO-PENDING APPLICATION

This application is a continuation of U.S. application Ser. No. 10/790,952 filed Mar. 2, 2004, now U.S. Pat. No. 7,109,987 entitled "Method and Apparatus for Dual Pass Adaptive Tessellation," having as inventors Vineet Goel, Robert Scott Hartog, and Stephen Morein, and owned by instant Assignee.

FIELD OF THE INVENTION

The present invention relates generally to graphics rendering and, more specifically, to the generation of standardized tessellation factors for rendering an image.

BACKGROUND OF THE INVENTION

In a graphics processing system, objects to be displayed are generally represented by a collection of polygons. Polygons are generally chosen due to the existence of efficient algorithms for the rendering thereof. However, the object that is approximated by polygons is frequently a curved shape. Most methods for describing these surfaces fall under the classification of "higher order surfaces" (HOS).

Patches, such as a Bezier patch, may represent a surface of an object. These are one representative type of HOS. These patches may typically contain information beyond standard pixel information and may further include information relating to surface normals, lighting source orientation, surface color and opacity, and coordinates of a texture image to be mapped onto the surface. Subdividing the patches until the subpatches are sufficiently flat so they may be approximated by a quadrilateral may be used to render the HOS or any other criterion to subdivide patches to render. The subpatches may then be divided into triangles for graphics processing.

Another problem is the relative location of the object, such as a primitive, within a viewable output screen. The primitive, such as a triangle, defines an area and includes a plurality of pixels. Due to the size of the primitive and the location of the primitive within a rendered scene, the ratio of the number of pixels relative to the primitive may be skewed.

As primitives may be deeper within the rendered scene, such as having a smaller depth value, the ratio of pixels per primitive may be reduced. During the rendering of the pixels, the depth offset may adversely affect the computation of tessellation factors. Using an adaptive tessellation technique, various adaptive tessellation factors may be computed using a software algorithm. However, the technique includes processing time limitations and further includes space limitations as there must be physical space within a graphics processing system for a processor, such as a general purpose processor, executing operating instructions for calculating the adaptive tessellation factors.

Therefore, during the processing of tessellation factors, this technique may be inefficient as it requires offloading of vertex information, computation of the adaptive tessellation factors, and loading these tessellation factors back into the processing pipeline.

Another approach utilized for generating tessellation factors is an independent hardware configuration, which interfaces with the graphics rendering pipeline. This hardware approach provides a separate processor in communication with the graphics rendering pipeline and thus not only requires valuable real estate for the extra hardware, but also requires further processing time for the transmission of primi-

2

tive indices to the hardware device and the transmission of vertex tessellated data back to the processing pipeline.

During the generation of tessellation factors, there are also limitations regarding the adaptability of the tessellation engine to perform discrete tessellation, continuous tessellation, and adaptive tessellation. Current solutions provide for a tessellation engine to be designated for performing a predetermined type of tessellation, thereby only allowing for the reception of limited primitive types and thereby limited tessellation patterns.

As such, there exists a need for generating tessellation factors independent of the primitive types, wherein the tessellation factor generation efficiently uses existing available processing resources without adversely affecting system processing speeds.

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention will be more readily understood with reference to the following drawings, wherein:

FIG. 1 illustrates an apparatus for dual pass adaptive tessellation as configured during a first pass in accordance with one embodiment of the present invention;

FIG. 2 illustrates the apparatus for dual pass adaptive tessellation as configured during a second pass in accordance with one embodiment of the present invention;

FIG. 3 illustrates a memory storing tessellation and index information in accordance with one embodiment of the present invention;

FIG. 4 illustrates a flow chart of the steps of a method for dual pass adaptive tessellation in accordance with one embodiment of the present invention; and

FIG. 5 illustrates a flow chart of the steps of another method for dual pass adaptive tessellation in accordance with another embodiment of the present invention.

DETAILED DESCRIPTION OF A PREFERRED EMBODIMENT

FIG. 1 illustrates an apparatus **100** for dual pass adaptive tessellation. The apparatus **100** includes a memory interface **102**, a global register bus **104**, and a vertex grouper tessellator **106** having a direct memory access engine **108** disposed therein. The apparatus **100** further includes a shader processing unit **110**, a plurality of vertex shader input staging registers **112** coupled to a plurality of vertex shaders **114**, and a memory **116** coupled to the shaders **114** across a bus **118**. The shader processing unit **110** may be a sequencer or a control flow processor. Moreover, each of the shaders **114** includes a math processing unit, which may be any suitable processing unit capable of executing mathematical operations.

In one embodiment, the vertex grouper tessellator **106** is pass-through enabled for a first pass. During the first pass, an index list **120** is provided from the memory interface **102** to the direct memory access engine **108**. Furthermore, vertex grouper tessellator state data, direct memory access request data, and a draw initiator **122** are received from the global register bus **104** by the vertex grouper tessellator **106**. The indices of primitives are sent through the vertex grouper tessellator **106** to be loaded into registers of shader pipes, such as registers **112** and shaders **114**. The vertex grouper tessellator **106** also sends an auto-index value for each primitive to one of the shader registers **112**. More specifically, the vertex grouper tessellator **106** provides primitive information **124** to the shader sequencer **110**, which thereupon distributes partitioned information **126** to each of the vertex shader input state registers **112**.

The vertex grouper tessellator **106**, during a first pass, also generates a per process vector **130**, per primitive data **132** and per packet data **134**. During the first pass, no pixels are generated, but the signals **130-134** may still have to pass synchronization signals for vertex and state deallocation.

Referring to the shader pipeline, the vertex shaders **114** receive vertex data arrays **134** retrieved from the memory **116**. The shader processing unit **110** fetches corner vertices of high order surface primitives and computes tessellation factors based on corner vertices of edges of primitives. In another embodiment, during the first pass, the vertex shaders **114** also generate control points for high order surfaces. The tessellator **106** is disabled during this pass.

Each of the vertex shaders **114** thereupon provides these computed values. In one embodiment, original indices **136** are written to the memory **116** across the bus **118** at indexed location as specified by an auto-index value. In one embodiment, the control points and tessellation factors are written in separate linear buffers.

During the second pass, more than one index can be passed to the vertex grouper tessellator **106** along with primitive types such as tri-list, quad-list, line-list, rect-patch, line-patch, or tri-patch. The vertex grouper tessellator **106** generates the parametric coordinates (u, v) for tensor products surfaces or barycentric coordinates (u, v, w) for triangular surfaces using tessellation factors computed during the first pass. These coordinates, along with original indices and/or an auto-index value, are passed to the shader register **112** for evaluating tessellated vertices based on user evaluation shaders. The tessellation engine **100** also generates subprimitive information for clipper and primitive assemblers for paths **134**, **132**, **130**.

FIG. 2 illustrates the apparatus **100** through a second pass, with the vertex grouper tessellator **106** being enabled. The memory interface **102** receives a plurality of tessellation factors **150** received from the memory **116** of FIG. 1. Using the direct memory access engine **108** within the vertex grouper tessellator **106**, the tessellation factors are retrieved by a direct memory access request **152**, wherein the tessellation factors are provided for the vertex grouper tessellator **106** operating in an adaptive mode. In this second pass, the tessellation factors **150** are accessed as indices and an auto-index **124** is generated, wherein the auto-index **124** is loaded to the registers **112** of the shaders **114**. A primitive mode indicator is set to a tessellation mode such that the indices that go to the tessellation engine are interpreted as tessellation factors. The vertex group tessellator **106** generates barycentric or tensor coordinates, which are loaded to the shader registers **112** along with the auto-index value. The shaders **114** compute the tessellated vertices by fetching control points from locations specified by the auto-index value and using barycentric or tensor product coordinates.

In one embodiment, a primitive data array **154** is retrieved from memory such that the vertex shaders **114** may be utilized for the generation of newly computed subprimitive information **156**.

The vertex grouper tessellator **106** further generates the vector information **130**, primitive information **132**, and packet information **134**. The per process vector information **130** includes state context vector and process vector size information. The per primitive information **132** includes subprimitive assembly data including internal vertex indices, end of packet information, and deallocation information. The per packets information **134** includes state context vector and a subprimitive type information.

Therefore, by using a dual pass system for adaptive tessellation, the vertex grouper tessellator **106** is disabled in a pass-through mode for generating tessellation factors using the shaders **114** during pass one and the tessellator part of vertex grouper tessellator **106** is enabled in a tessellator mode for the second pass such that the tessellation factors themselves are used to generate tessellation outputs such as the per process vector output, the per primitive output and the per packet output in conjunction with the subprimitive data **156**. As such, the present invention utilizes a single tessellation engine **100** and reuses the same engine with different primitive types to generate the needed output. Therefore, the present invention not only reduces the amount of real estate needed for hardware components, the engine **100** improves processing efficiency by allowing for the generation of tessellation output within the pixel/vertex processing pipeline.

The tessellation engine also generates vertices based on a vertex reuse number available to it, thereby providing for a scalable design. In one embodiment, a vertex reuse number may be a data indicator indicating the availability of reutilizing vertex information, which may be stored within an internal memory. The present invention allows for a compact design of the tessellation engine, a form of programmable tessellation where evaluation part can be specified by an end user. The present invention further includes a large range of primitive types per tessellation and a form of device capable of allowing data explosion by generating more vertices in providing subprimitive information.

In one embodiment, the tessellation engine **100** is a fixed-function block. This engine **100** understands a finite set of modes, each of which is defined for a specific purpose. The below table shows all of the modes supported by the present invention. As recognized by one having ordinary skill in the art, the below table indicates various modes for exemplary purposes only and illustrates one embodiment of the present invention. As recognized by one having ordinary skill in the art, any other suitable implementation in accordance with the information listed below for adaptive tessellation may also be suitably implemented within the scope of the present invention.

Mode Name	Tessellator Input						Tessellator Output			
	Prim Type	Index (from Memory PG)	Two Cycle Input	Cycle 0		Cycle 1	Two Cycle Output Mode	Tess Output (all fixed)	VTG Output Prim Type	VGT Output (all floats)
	Size		Mode							
Line List - Single	2	std	0	2 std	—		0	2 std	Line List	2 indx
Tri List - Single	4	std	0	3 std	—		1	3 std	Tri List	3 indx
				indx				indx		3 coord

-continued

Mode Name	Tessellator Input					Tessellator Output			
	Prim Type (from PG)	Index Memory Size	Two Cycle Input Mode	Cycle 0	Cycle 1	Two Cycle Output Mode	Tess Output (all fixed)	VTG Output Prim Type	VGT Output (all floats)
Quad List - Single	13	std	1	3 std indx	1 std indx	1	4 std indx	Tri List	4 indx 2 coord
L-Patch - Single	24	std	0	1 std indx	—	0	1 std indx	Line List	1 std indx 1 coord
T-Patch - Single Pass	25	std	0	1 std indx	—	1	1 std indx	Tri List	1 std indx 1 quad id 3 coord
R-Patch - Single Pass	26	std	0	1 std indx	—	1	1 std indx	Tri List	1 std indx 1 quad id 2 coord
Last of Multi-pass	24	—	0	1 auto-index	—	0	1 auto-index	Line List	1 auto 1 quad id 1 coord
Last of Multi-pass	24	1 tess factor (float)	0	1 tess factor (float)	—	0	1 auto-index		1 auto 1 quad id 1 coord
Last of Multi-pass	25	—	0	1 auto-index	—	1	1 auto-index	Tri List	1 auto 1 quad id 3 coord
Last of Multi-pass	25	3 tess factors (float)	1	3 tess factors (float)	1 auto-index	1	1 auto-index		1 auto 1 quad id 2 coord
Last of Multi-pass	26	—	0	1 auto-index	—	1	1 auto-index	Tri List	1 auto 1 quad id 2 coord
Last of Multi-pass	26	4 tess factors (float)	1	3 tess factors (float)	1 tess factor 1	1	1 auto-index		1 auto 1 quad id 2 coord

In one embodiment, the tessellatuiou engine **100** was enabled by selecting the tessellation engine path in a output path control register, indicated either continuous, discrete, or adaptive. The tessellation engine also specifies a maximum tessellation level. For adaptive tessellation mode, this is the maximum tessellation clamp value. For continuous and discrete tessellation mode, this is a tessellation level. For the adaptive tessellation mode, there is a minimum tessellation clamp value. For continuous and discrete tessellation loads, this register is not applicable in this embodiment of this present invention.

FIG. 3 illustrates an exemplary embodiment of a data field **200** that may be stored in the memory **116** of FIG. 1. The data **200** includes a tessellation factor field **202** storing three tessellation factors **204** for a triangle primitive type and an original indices field **206** storing original indices **208**. The data field **200** further includes a base address **210** for reference of the tessellation factor therefrom. The tessellation factors **202** and the original indices **206** may have a data size relative to the corresponding number of vertex shaders **114** of FIG. 2 such that the associated tessellation information may be generated therefrom. It is recognized by one having ordinary skill in the art that any other suitable memory data structure may be implemented and that the data structure **200** of FIG. 3 is for illustration purposes only.

FIG. 4 illustrates the steps of the method for dual pass adaptive tessellation. The method begins, step **220**, by receiving vertex information and an index list, wherein the index list is received from a memory device in step **222**. With reference to FIG. 1, index list **120** is retrieved from a memory interface across a direct memory access engine **108**. The next step, step **224**, consists of generating primitive indices from the vertex information and an auto-index value for each of the primitive

indices. Also from the first pass, the next step is generating a plurality of shader sequence outputs **226**. Illustrated with reference to FIG. 1, the plurality of shader sequence outputs **126** are provided to the plurality of vertex shader input staging registers **112**, step **228**. Therefore, within the first pass, a plurality of tessellation factors are generated in response to shader sequence output, step **230**.

The vertex shader output **136**, in one embodiment, is stored in a memory such that it may be further received as a plurality of indices, step **232**, during a second pass. As illustrated in FIG. 2, the tessellation factors **150** are provided to the memory interface **102** such that they may be retrieved from the direct memory access engine **108**. As such, one embodiment of the method is complete, step **234**.

FIG. 5 illustrates another embodiment of a method for dual pass adaptive tessellation. The method begins, step **250**, by performing steps **222** through **230** of FIG. 4, step **252**. As discussed above, these first pass steps include receiving primitive information, an index list, and an auto-index value for each of the primitive indices, generating a plurality of shader sequence outputs, providing the shader sequence outputs to a plurality of vertex shader input staging registers, and generating a plurality of tessellation factors in response to the shader sequence outputs. The next step, step **254**, is writing the plurality of tessellation factors to a memory device. As discussed above with respect to FIG. 1, the memory **116** may be any suitable memory device capable of storing and allowing retrieval of the tessellation factors therefrom. Steps **252** and **254**, in the present embodiment, occurred during a first pass of the tessellation engine **100** of FIGS. 1 and 2.

During a second pass, the first step, step **256**, is receiving the tessellation factors from the memory device. The next step, step **258**, is generating an auto-index value for each of

7

the plurality of indices. The next step, step **260**, is generating a plurality of barycentric coordinates based on the tessellation factors, or in another embodiment, tensor product coordinates may be computed based on primitive type. As discussed above, the coordinates may be (u, v) or (u, v, w) based on the higher order surface. 5

Still within the second pass, the next step, step **262**, is computing a plurality of tessellated vertices by fetching a control point specified by the auto-index value for each of the plurality of indices. In one embodiment, the control point specified by the auto-index value for each of the plurality of indices may be disposed within the memory **116** illustrated in FIG. **1** and provided to the vertex shaders **114**. As such, output signals **130**, **132**, and **134** are generated by the vertex grouper tessellator **106** of FIG. **1** and subprimitive data are further generated by the vertex shaders **114** of FIG. **2**. 10 15

It is understood that there exist implementations of other variations and modifications of the invention and its various aspects, as may be readily apparent to those of ordinary skill in the art, and that the invention is not limited by the specific embodiments described herein. For example, the number of vertex shaders and vertex shader instruction staging registers may be adjusted based on the number of tessellation factors to be computed, and the shader processing unit output may also be adjusted to correspond to the number of vertex shaders and vertex shader instruction staging registers. It is therefore contemplated and covered by the present invention any and all modifications, variations, or equivalents that fall within the scope of the basic underlying principles disclosed and claimed herein. 20 25 30

What is claimed is:

1. An apparatus for dual pass adaptive tessellation comprising:

a vertex grouper tessellator operatively coupled to a plurality of vertex shaders wherein, during a first pass:

8

the vertex grouper tessellator is operative to generate primitive indices and corresponding auto-index values based on primitive information and an index list; and

the plurality of vertex shaders are operative to generate tessellation factors based on the primitive indices and the corresponding auto-index values.

2. The apparatus of claim **1**, wherein during the first pass the vertex grouper tessellator is further operative to generate at least one of: a per process vector output, a per primitive output and a per packet output.

3. The apparatus of claim **1**, further comprising:

a shader processing unit such that during the first pass the shader processing unit is operative to generate a shader sequence output based on the primitive indices and the corresponding auto-index values; and

wherein the plurality of vertex shaders are operative to generate tessellation factors based on the shader sequence output.

4. The apparatus of claim **1**, wherein, during a second pass: the vertex grouper tessellator, based on the plurality of tessellation factors, is operative to generate coordinates for at least one surface and an auto-index value for each of the plurality of tessellation factors; and

the plurality of vertex shaders are operative to generate tessellation vertices for the at least one surface based at least on the generated coordinates and the auto-index values corresponding to the plurality of tessellation factors.

5. The apparatus of claim **4**, wherein the plurality of vertex shaders are operative to fetch control points specified by the auto-index values corresponding to the plurality of tessellation factors, and wherein the tessellation vertices are generated based on the generated coordinates and the control points. 35

* * * * *